

Technical Leaflet



CaSoPaL® clean Disinfectant

Properties

CaSoPaL® clean consists of a mixture of ethanol, iso-propanol and water and is used to disinfect wallpapers and loose paints. CaSoPaL® clean can be processed by spraying or brushing, also wiping with a cloth saturated with CaSoPaL® clean is possible. Disinfection is achieved within few minutes.

Application instructions

Successful removal of microbiological growth requires complete elimination of the source. The earlier the mould is removed, the easier it is to keep it under control. When mould is found on wallpapers or loose paint layers, it can be expected that the source is much greater than visible. It is necessary to remove the wallpaper and loose layers – but without contamination of surrounding areas. This can be achieved by applying CaSoPaL® clean, which kills bacteria, viruses, fungi and algae. The infected areas have to be fully saturated. Wallpapers and loose layers can be removed after evaporation of the alcohols, they should be given into plastic bags which must be tightly closed. Open the windows during application and follow the safety instruction given below. In a second step, areas behind the wallpaper have to be treated with CaSoPaL® plus followed by coating with CaSoPaL® Anti-Mould Paint.

Packaging

CaSoPaL® clean is available in 500 mL spray flasks as well as 500 mL, 1 L, 5 L and 10 L containers.

Storage

Storable for at least 5 years in closed original containers. Keep away from moisture and air. CaSoPaL® clean has to be stored between +5 °C and +30 °C.

Safety instructions

CaSoPaL® clean is flammable/combustible. Keep away from oxidisers, heat, sparks and flames. Avoid spilling, skin and eye contact. Use face mask, protective gloves and safety glasses. Spraying may produce aerosols which can be dangerous and harmful to health. Ventilate well, avoid breathing vapours. Open the windows. Keep the containers tightly close. Keep out of reach of children. Follow the instructions given in our Material Safety Data Sheet.

Biocide-Number (Germany): N-59051

The information mentioned above is state of the art and has been developed by intensive research and development. The application of our products and their use is beyond the range of our influence. Therefore IBZ-Salzchemie GmbH & Co. KG cannot take any liability from events that result from the information contained in this leaflet. Careful and considered use of CaSoPaL® clean is highly recommended.



IBZ-Salzchemie GmbH & Co.KG

Schwarze Kiefern 4 • D-09633 Halsbrücke • Germany • Tel.: +49 3731 200155 • Fax: +49 3731 200156
www.ibz-freiberg.de • info@ibz-freiberg.de